



P=9.50mm, N为孔位数(N for hole digits), 有效位数为(Significant Digits): 02P~XXP

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	19.00	28.50	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.50	114.00	123.50
B	9.50	19.00	28.50	38.00	47.50	57.00	66.50	76.00	85.50	95.00	104.50	114.00
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	...
L	133.00	142.50	152.00	161.50	171.00	180.50	190.00	199.50	209.00	218.50	228.00	
B	123.50	133.00	142.50	152.00	161.50	171.00	180.50	190.00	199.50	209.00	218.50	

版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/30A	1000V/32A
压线范围 (Wire Range)	26~10AWG	4.0mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	8mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	
方盒 (Gage)	铜合金, 镀镍 (Copper alloy, Ni plated)	

产品命名编码:  
(Product Number Code):

GS008-9.5-XXP-1Y-00A (H)

产品型号 (Series No.) | 客户需求 (Customer Request)  
极数 (No. of poles) | 塑体颜色 (Housing Color)

- |                        |                       |
|------------------------|-----------------------|
| 1: 单倍间距 (Single Pitch) | 7: 透明色 (Transparent)  |
| 2: 双倍间距 (Double Pitch) | 8: 白色 (White)         |
|                        | 9: 黄色 (Yellow)        |
|                        | Y: 多种颜色 (Mixed Color) |
|                        | 3: 黑色 (Black)         |
|                        | 4: 灰色 (Grey)          |
|                        | 5: 橙色 (Orange)        |
|                        | 6: 红色 (Red)           |

<b>宁波高胜电子有限公司</b> <b>NINGBO GOOSVN ELECTRONIC CO.,LTD</b>		公差范围 (Tolerance Range)
型号 (Type): GS008-9.5-XXP-1Y-00A (H)		150~ ±1.50
核准 (Approval):		60~150 ±1.00
图号 (Drawing NO.):		30~60 ±0.60
审核 (Audit):		6~30 ±0.40
单位 (Units): mm		0~6 ±0.25
页码 (Page): 1/1		角度 (Angle) X ±2°
设计 (Design):		XX ±1°
比例 (Scale): FULL		版次 (Version): T0