



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	150V/4A	250V/5A
压线范围 (Wire Range)	/	/
工频耐压 (Frequency Voltage)	AC 1300V	
冲击耐压 (Rated Surge Voltage)	2500V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	/	
工作温度 (Temperature)	-40℃~+105℃	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
/	/	

产品命名编码:

(Product Number Code):

GSP002RH-2.5-2*XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求 (Customer Request)

极数 (No. of poles)

塑体颜色 (Housing Color)

- 1: 单倍间距 (Single Pitch)
- 2: 双倍间距 (Double Pitch)

- 1: 绿色 (Green)
- 2: 蓝色 (Blue)
- 3: 黑色 (Black)
- 4: 灰色 (Grey)
- 5: 橙色 (Orange)
- 6: 红色 (Red)
- 7: 透明色 (Transparent)
- 8: 白色 (White)
- 9: 黄色 (Yellow)
- Y: 多种颜色 (Mixed Color)

P=2.50mm, N为孔位数 (N for hole digits); 有效位数为 (Significant Digits): 2* (02P~24P)

N	2*02P	2*03P	2*04P	2*05P	2*06P	2*07P	N	2*08P	2*09P	2*10P	2*11P	2*12P	2*13P
L	6.90	9.40	11.90	14.40	16.90	19.40	L	21.90	24.40	26.90	29.40	31.90	34.40
B	2.50	5.00	7.50	10.00	12.50	15.00	B	17.50	20.00	22.50	25.00	27.50	30.00
N	2*14P	2*15P	2*16P	2*17P	2*18P	2*19P	N	2*20P	2*21P	2*22P	2*23P	2*24P	
L	36.90	39.40	41.90	44.40	46.90	49.40	L	51.90	54.40	56.90	59.40	61.90	
B	32.50	35.00	37.50	40.00	42.50	45.00	B	47.50	50.00	52.50	55.00	57.50	

宁波高胜电子有限公司
NINGBO GOOSVN ELECTRONIC CO.,LTD

公差范围 (Tolerance Range)

150~	±1.50
60~150	±1.00
30~60	±0.60
6~30	±0.40
0~6	±0.25

型号 (Type): GSP002RH-2.5-2*XXP-1Y-00A (H)

核准 (Approval): _____ 图号 (Drawing NO.): _____

审核 (Audit): _____ 单位 (Units): mm 页码 (Page): 1/1

设计 (Design): _____ 比例 (Scale): FULL

版次 (Version): T0