


版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	600V/15A	750V/24A
压线范围 (Wire Range)	20~14AWG	0.5~2.5mm ²
工频耐压 (Frequency Voltage)	AC 3000V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	/	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-2)	
接线柱 (Contact Block)	铜合金, 镀镍 (Copper alloy, Ni plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	

产品命名编码:

(Product Number Code):

GSS100W-8.0-XXP-1Y-00A (H)



- | | | | | | |
|------------------------|------------------------|----------------------|---------------|----------------|-----------------------|
| 1: 单倍间距 (Single Pitch) | 2: 双倍间距 (Double Pitch) | 7: 透明色 (Transparent) | 8: 白色 (White) | 9: 黄色 (Yellow) | Y: 多种颜色 (Mixed Color) |
| 3: 绿色 (Green) | 4: 蓝色 (Blue) | 5: 黑色 (Black) | 6: 灰色 (Grey) | 6: 红色 (Red) | |

P=8.00mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~12P

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P
L	13.70	21.70	29.70	37.70	45.70	53.70	61.70	69.70	77.70	85.70	93.70
B	8.00	16.00	24.00	32.00	40.00	48.00	56.00	64.00	72.00	80.00	88.00

宁波高胜电子有限公司 NINGBO GOOSVN ELECTRONIC CO.,LTD		公差范围 (Tolerance Range)	
		150~	±1.50
型号 (Type): GSS100W-8.0-XXP-1Y-00A (H)		60~150	±1.00
核准 (Approval):		30~60	±0.60
图号 (Drawing NO.):		6~30	±0.40
审核 (Audit):		0~6	±0.25
单位 (Units): mm		角度 (Angle):	X ±2°
页码 (Page): 1/1		XX	±1°
设计 (Design):		比例 (Scale): FULL	版次 (Version): T0