



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/20A	630V/32A
压线范围 (Wire Range)	22~12AWG	4.0mm ²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀镍 (Steel, Nickel plating)	

产品命名编码: (Product Number Code):

GSA55RW-10.0-XXP-1Y-00A (H)

产品型号 (Series No.): GSA55RW-10.0-XXP-1Y-00A (H)

客户需求 (Customer Request): 00A (H)

极数 (No. of poles): 10.0

塑体颜色 (Housing Color): Y

1: 单倍间距 (Single Pitch)	2: 双倍间距 (Double Pitch)	7: 透明色 (Transparent)	8: 白色 (White)
3: 绿色 (Green)	4: 蓝色 (Blue)	9: 黄色 (Yellow)	Y: 多种颜色 (Mixed Color)
5: 橙色 (Orange)	6: 红色 (Red)		

PCB LAYOUT

P=10.0mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P~22P

	N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00	120.00	130.00	140.00	150.00	
B	10.00	20.00	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00	120.00	
D	30.00	40.00	50.00	60.00	70.00	80.00	90.00	100.00	110.00	120.00	130.00	140.00	
N	14P	15P	16P	17P	18P	19P	20P	21P	22P				
L	160.00	170.00	180.00	190.00	200.00	210.00	220.00	230.00	240.00				
B	130.00	140.00	150.00	160.00	170.00	180.00	190.00	200.00	210.00				
D	150.00	160.00	170.00	180.00	190.00	200.00	210.00	220.00	230.00				

GOOSVN 宁波高胜电子有限公司
NINGBO GOOSVN ELECTRONIC CO.,LTD

型号 (Type): GSA55RW-10.0-XXP-1Y-00A (H)

核准 (Approval): _____ 图号 (Drawing NO.): _____

审核 (Audit): _____ 单位 (Units): mm 页码 (Page): 1/1

设计 (Design): _____ 比例 (Scale): FULL

公差范围 (Tolerance Range):

150~	±1.50
60~150	±1.00
30~60	±0.60
6~30	±0.30
0~6	±0.25

角度 (Angle): X ±2°
 XX ±1°

版次 (Version): T0