



版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

P=9.5mm, N为孔位数 (N for hole digits),
有效位数为 (Significant Digits): 02P~24P

N	02P	03P	04P	05P	06P	07P
L	20.30	29.80	39.30	48.80	58.30	67.80
B	9.50	19.00	28.50	38.00	47.50	57.00
N	14P	15P	16P	17P	18P	19P
L	134.30	143.80	153.30	162.80	172.30	181.80
B	123.50	133.00	142.50	152.00	161.50	171.00
N	08P	09P	10P	11P	12P	13P
L	77.30	86.80	96.30	105.80	115.30	124.80
B	66.50	76.00	85.50	95.00	104.50	114.00
N	20P	21P	22P	23P	24P	
L	191.30	200.80	210.30	219.80	229.30	
B	180.50	190.00	199.50	209.00	218.50	

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/20A	630V/32A
压线范围 (Wire Range)	22~12AWG	4.0mm ²
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	6000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	6~7mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plating)	
螺丝 (Screws)	钢, 镀镍 (Steel, Nickel plating)	

产品命名编码:

(Product Number Code):

GSA9500S-9.5-XXP-1Y-00A (H)

产品型号 (Series No.)

客户需求
(Customer Request)

极数 (No. of poles)

塑体颜色 (Housing Color)

- 1: 单倍间距 (Single Pitch)
- 2: 双倍间距 (Double Pitch)

- 7: 透明色 (Transparent)
- 8: 白色 (White)
- 9: 黄色 (Yellow)
- Y: 多种颜色 (Mixed Color)
- 1: 绿色 (Green)
- 2: 蓝色 (Blue)
- 3: 黑色 (Black)
- 4: 灰色 (Grey)
- 5: 橙色 (Orange)
- 6: 红色 (Red)

宁波高胜电子有限公司 NINGBO GOOSVN ELECTRONIC CO.,LTD		公差范围 (Tolerance Range)	
型号 (Type): GSA9500S-9.5-XXP-1Y-00A (H)	核准 (Approval):	图号 (Drawing NO.):	150~ ±1.50
审核 (Audit):	单位 (Units): mm	页码 (Page): 1/1	60~150 ±1.00
设计 (Design):	比例 (Scale): FULL	角度 (Angle): X ±2° XX ±1°	30~60 ±0.60
		版次 (Version): T0	6~30 ±0.40
			0~6 ±0.25