



技术参数 (Technical Data)		
项 目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/10A	450V/12A
压线范围 (Wire Range)	28~12AWG	2.5mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤20mΩ	
剥线长度 (Stripping Length)	6mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PA66 (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺钉 (Screwing)	不锈钢 (Stainless)	

产品命名编码:

(Product Number Code):

GSL008H2-5.0-2\*XXP-1Y-00A (H)

产品型号 (Series No.)      客户需求 (Customer Request)  
 极数 (No. of poles)      塑体颜色 (Housing Color)

- |                           |                          |
|---------------------------|--------------------------|
| 1: 单倍间距<br>(Single Pitch) | 7: 透明色<br>(Transparent)  |
| 2: 双倍间距<br>(Double Pitch) | 8: 白色 (White)            |
|                           | 9: 黄色 (Yellow)           |
|                           | Y: 多种颜色<br>(Mixed Color) |

L为总长, P为PIN距, N为位数 (有效位数为02P~XXP), P=5.00mm

N	02P	04P	06P	08P	10P	12P	14P	16P	18P	20P	22P	24P	
L	6.00	11.00	16.00	21.00	26.00	31.00	36.00	41.00	46.00	51.00	56.00	61.00	
B	/	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	
D	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	
N	26P	28P	30P	32P	34P	36P	38P	40P	42P	44P	46P	48P	...
L	66.00	71.00	76.00	81.00	86.00	91.00	96.00	101.00	106.00	111.00	116.00	121.00	
B	60.00	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	
D	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	120.00	

<b>宁波高胜电子有限公司</b> NINGBO GOOSVN ELECTRONIC CO.,LTD	公差范围 (Tolerance Range)	
	150~	±1.50
型号 (Type): GSL008H2-5.0-2*XXP-1Y-00A (H)	60~150	±1.00
	30~60	±0.60
核准 (Approval):	6~30	±0.40
	0~6	±0.25
审核 (Audit):	角度 (Angle)	X ±2°
	XX	±1°
设计 (Design):	单位 (Units): mm	页码 (Page): 1/1
	比例 (Scale): FULL	版次 (Version): T0