

P=5.00mm, N为孔位数 (N for hole digits), 有效位数为 (Significant Digits): 02P, 03P~XXP

N	02P	03P	04P	05P	06P	07P	08P	09P	10P	11P	12P	13P
L	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00
B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
N	14P	15P	16P	17P	18P	19P	20P	21P	22P	23P	24P	...
L	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	120.00	
B	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.00	105.00	110.00	115.00	


版次 (Version)	变更内容 (Rev. Content)	变更者 (Change Person)

技术参数 (Technical Data)		
项目 (Item)	UL	IEC
额定电气参数 (Rated Electrical Parameters)	300V/20A	250V/24A
压线范围 (Wire Range)	22~12AWG	2.5mm <sup>2</sup>
工频耐压 (Frequency Voltage)	AC 2500V	
冲击耐压 (Rated Surge Voltage)	4000V	
绝缘阻抗 (Insulation Resistance)	DC500V 500MΩ above	
接触电阻 (Contact Resistance)	≤8mΩ	
剥线长度 (Stripping Length)	5~6mm	
工作温度 (Temperature)	-40°C~+105°C	
材质和电镀 (Material and plating)		
绝缘材质 (Housing)	PC (UL94 V-0)	
触点材料 (Contact)	铜合金, 镀锡 (Copper alloy, Sn plated)	
螺丝 (Screws)	钢, 镀锌 (Steel, Zn plated)	
弹片 (Spring)	不锈钢 (Stainless)	

产品命名编码:

(Product Number Code):

GS023-5.0-XXP-1Y-00A (H)



- 1: 单倍间距 (Single Pitch)  
2: 双倍间距 (Double Pitch)

- 1: 绿色 (Green)      7: 透明色 (Transparent)  
2: 蓝色 (Blue)      8: 白色 (White)  
3: 黑色 (Black)     9: 黄色 (Yellow)  
4: 灰色 (Grey)      Y: 多种颜色 (Mixed Color)  
5: 橙色 (Orange)  
6: 红色 (Red)

**GOOSVN** 宁波高胜电子有限公司 NINGBO GOOSVN ELECTRONIC CO.,LTD

型号 (Type): GS023-5.0-XXP-1Y-00A (H)

核准 (Approval): \_\_\_\_\_ 图号 (Drawing NO.): \_\_\_\_\_

审核 (Audit): \_\_\_\_\_ 单位 (Units): mm 页码 (Page): 1/1

设计 (Design): \_\_\_\_\_ 比例 (Scale): FULL

公差范围 (Tolerance Range):  
150~ ±1.50  
60~150 ±1.00  
30~60 ±0.60  
6~30 ±0.40  
0~6 ±0.25

角度 (Angle): X ±2°  
XX ±1°

版次 (Version): T0